



TEXAS A&M  
**AGRILIFE**  
RESEARCH | EXTENSION

## DUAL-FLUSH TOILET

# URBAN WATER PROGRAM

### **New homes are already mandated to have low-flow toilets.**

However, dual-flush toilets use less water than low-flow toilets and have more flushing power.

### **What is a dual-flush toilet?**

- Dual-flush toilets have two buttons: full flush and half flush.
- Full flush uses 1.6 gallons per flush (solid) and half flush uses 0.8 gallons per flush (liquid).

### **This makes the average flush only 1 gallon!**

- A single rubber washer replaces the traditional flapper valve, the cause of most toilet problems. The dual-flush mechanism slides out for easy replacement.
- The toilet has a quiet, no-noise siphon jet.
- Bowl wash keeps the unit cleaner, reducing the need for cleaning chemicals.
- A 4-inch trap helps prevent clogs. In other toilets, traps may be as small as 1.5 inches.

### **Dual-flush toilets can easily be installed or retrofitted in your house.**

- Toilets come in a variety of models, one to fit every budget.
- Most models can be connected to a drain hole centered either 10 inches or 12 inches from the wall. Older homes often have holes 10 inches from the wall; today, 12 inches is the standard.
- The fill valve is a standard brand. Any hardware store could probably supply a replacement.
- You can buy dual-flush toilets at several locations in the Dallas/Fort Worth area.

Texas A&M AgriLife Research  
and Extension Center at Dallas  
17360 Coit Rd, Dallas, TX 75252  
(972) 952-9671 Office  
(972) 952-9216 Fax  
Email: [urbanwater@tamu.edu](mailto:urbanwater@tamu.edu)  
<http://dallas.tamu.edu>